



Bearing No.	Dimensions(mm)									Basic Load rating(KN)		Weight(g)
	d	d2	B	C1	d3	L1	L2	L	d1	Cd	Cs	
SA5T/K	5	18	8	6	M5X0.8	33	19	42	7.7	4	7.5	13
SA6T/K	6	20	9	6.75	M6X1	36	22	46	8.9	4.4	9.3	20
SA8T/K	8	24	12	9	M8X1.25	42	25	54	10.4	8	16.7	33
SA10T/K	10	28	14	10.5	M10X1.5	48	29	62	12.9	12.9	23.4	56
SA12T/K	12	32	16	12	M12X1.75	54	33	70	15.4	17	32	87
SA14T/K	14	36	19	13.5	M14X2	60	38	78	16.8	24	41.9	129
SA16T/K	16	42	21	15	M16X2	66	40	87	19.3	28.5	52.7	189
SA18T/K	18	46	23	16.5	M18X1.5	72	44	95	21.8	35	63.8	267
SA20T/K	20	50	25	18	M20X1.5	78	47	103	24.3	40	78.1	348
SA22T/K	22	54	28	20	M22X1.5	84	51	111	25.8	52	97.2	443
SA25T/K	25	60	31	22	M24X2	94	58	124	29.6	60	122.1	600
SA30T/K	30	70	37	25	M30X2	110	71	145	34.8	81	168.4	1030
SA35T/K	35	80	43	28	M36X2	125	77	165	37.7	100	205.7	1600